



See nothing, hear everything

Designed for wall-mounted left, centre and right speaker positions in a discreet home cinema system, CWM7.4 S2 can also be mounted beside, above or below the screen, ensuring crystal-clear dialogue and dramatic special effects. Thanks to Bowers & Wilkins unique QuickDogs™ fixing method, installation is simple, requiring no tools. Its 2.5-way configuration features a single Carbon Dome tweeter, twin 100mm (4in) Continuum cone midrange units and twin 100mm (4in) Aramid Fibre/paper bass cones.

Technical Specifications

Technical features	Carbon Dome tweeter Continuum midrange Aramid Fibre/Paper bass cones
Description	2½-way in-wall system
Drive units	1x ø25mm (1 in) Carbon Dome high-frequency 2x ø100mm (4 in) Continuum cone mid/bass 2x ø100mm (4 in) Aramid Fibre/Paper profile bass
Frequency range (-6dB)	-6dB at 43Hz - 33kHz
Frequency Response -3dB	45Hz - 28kHz ±3dB
Sensitivity	86dB spl (2.83Vrms, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 80Hz - 33kHz <0.5% 120Hz - 33kHz
Nominal impedance	8Ω (minimum 4.9Ω)
Recommended amplifier power	25W - 150W into 8Ω on unclipped programme
Frame height	625mm (24.6in)
Frame width	175mm (6.9in)
Depth (behind surface)	92.5mm (3.64in)
Cut-out height	597mm (23.5in)
Cut-out width	147mm (5.8in)
Protrusion	8mm (0.3in)
PMK	PMK CWMC7
Net weight	6.2kg (13.73 lb)
Finishes	Grille: White

